

# Aramus™ Single-Use 2D Bag Assemblies

*High-grade, gamma-stable fluoropolymer film provides higher purity and greater reliability*

The utilization of single-use (SU) systems continues to grow, and so do the purity concerns of the SU components and their potential impact on high-value final products. From the high cost of product loss due to assembly failures, to the challenges of maintaining compliance in an evolving global regulatory landscape, every angle requires protective measures.

Entegris brings a new level of assurance to your process. Our Aramus™ single-use assembly product design incorporates high purity, integrity, and performance standards of the microelectronics industry with the regulatory and quality requirements for life sciences. Entegris allows you to protect and store your high-value process solutions with reduced risk of product loss, contamination, and compromised quality.

Aramus single-use 2D bags are made of a high-grade, gamma-stable fluoropolymer, and provide high purity, exceptional compatibility, and increased safety for critical process fluids and final products. The innovative single-layer technology does not contain curing agents, antioxidants, plasticizers, or adhesives, so the potential for process fluid contamination is greatly reduced. These subassemblies withstand a wide operating temperature range (-196° to 121°C [-321° to 250°F] or lower), without negatively affecting the film; making them extremely durable in frozen applications.

Aramus single-use assemblies are manufactured in an ISO® Class 5 cleanroom and provide high purity, performance, quality, and safety for your process.



*Provides a new level of assurance for your frozen product.*

## APPLICATIONS

- Frozen product storage and shipment
- Cell culture freezing and storage
- Bulk product fill
- Critical buffer and media storage
- Process sampling and archiving
- Downstream bioprocessing



*Custom manifolding enables process efficiency in any application.*

FEATURES & BENEFITS

Wide temperature operating range	Maintains mechanical properties across a wide range of process temperatures.  Reduces bag breakage and can be used in cold temperature applications to -196°C (-321°F) or lower without negatively affecting bag or boat fitment.
Single-layer, fluoropolymer construction	Single-layer design does not delaminate, reducing the risk of material failures and product loss caused by delamination.  Exhibits chemical compatibility with a wide range of process chemicals including strong acids, strong bases, oils, lipids, and organic solves, without affecting the material or product.
Gamma-stable fluoropolymer film	Withstands market-standard gamma sterilization, from 25 to 40 kGy.
High-purity fluoropolymer materials	Reduces the number of potential contaminants (adhesives, binders, etc.) introduced to final product.  The high hydrophobicity of the fluoropolymer film has low potential to absorb active pharmaceutical ingredients and critical formulation excipients, reducing yield loss.  Have low particulates, low bioburden, and low endotoxin, increasing purity.
Manufactured in an ISO Class 5 certified cleanroom	Operators properly trained on gowning and handling procedures increases contamination control.  Mitigates contamination and maintains components low bioburden levels.
Multiple connectivity options	Provides greater flexibility when incorporating into an already validated process.



Multiple connectivity options enable process flexibility.

## SPECIFICATIONS


<b>Sterilization</b>	Gamma irradiation: 25 to 40 kGy		
<b>Dimensions*</b>		<b>LENGTH</b>	<b>WIDTH</b>
	20 mL	100 mm (3.9")	80 mm (3.1")
	50 mL	120 mm (4.7")	100 mm (3.9")
	100 mL	160 mm (6.3")	100 mm (3.9")
	250 mL	240 mm (9.4")	100 mm (3.9")
	500 mL	210 mm (8.3")	158 mm (6.2")
	1 L	285 mm (11.2")	178 mm (7.0")
	2 L	354 mm (13.9")	254 mm (10.0")
	5 L	470 mm (18.5")	323 mm (12.7")
	10 L	570 mm (22.4")	383 mm (15.1")
	20 L	718 mm (28.3")	483 mm (19.0")
	50 L	970 mm (38.2")	820 mm (32.3")
<b>Compliance</b>	Biological	USP <87>	Pass
		USP <88>	Pass
		USP Class VI	Pass
		USP <85> and EP 2.6.14	<0.125 EU/mL (based on 40 mL rinse)
		ISO 10993-4	Non-hemolytic
	Particulates	USP <788> and EP 2.9.19	Pass
	Extractables	USP <661>	Pass
	Animal origin	TSE/BSE	Compliant

\*Bag body dimensions listed. Tolerance of  $\pm 10$  mm on both height and width.

## CONFIGURATIONS


### Full Aramus Assembly Configuration Options

2-port: 20 mL, 50 mL, 100 mL, 250 mL




ITEM	DESCRIPTION
1	Aramus fluoropolymer film with hole for hanging
2	Fluoropolymer "boat" fitment with 2 hose barb ports
3	Tubing connection (BarbLock® clamp, Oetiker Stepless® clamp, or zip ties*)
4	Tubing 1/8" ID x 1/4" OD (AdvantaFlex® thermoplastic elastomer [TPE], AdvantaSil® silicone, Tygon® silicone, or C-Flex® 374 elastomer)
5	Pinch clamps
6	Tubing fittings 1/8" ID (Luer male/female with plugs)

3-port: 500 mL, 1 L



ITEM	DESCRIPTION
1	Aramus fluoropolymer film with slot for hanging
2	Fluoropolymer "boat" fitment with 3 hose barb ports
3	Tubing connection (BarbLock clamp, Oetiker Stepless clamp, or zip ties*)
4	Tubing for 500 mL, 1 L, and 2 L is 1/4" ID x 3/8" OD Tubing for 5 L, 10 L, 20 L, and 50 L* is 3/8" ID x 5/8" OD (AdvantaFlex TPE, AdvantaSil silicone, Tygon silicone, or C-Flex 374 elastomer)
5	Tubing for 500 mL, 1 L, and 2 L is 1/8" ID x 1/4" OD Tubing for 5 L, 10 L, 20 L, and 50 L* is 1/4" ID x 3/8" OD (AdvantaFlex TPE, AdvantaSil silicone, Tygon silicone, or C-Flex 374 elastomer)
6	Pinch clamps
7	Tubing fittings (Colder Product Company MPC male/female with plugs)
8	Tubing fittings (Luer male/female with plugs)
9	Rod (5 L, 10 L, 20 L, and 50 L*)

3-port: 2 L, 50 L\* (no rod),  
5 L, 10 L, 20 L, 50 L\* (with rod)




Note: See Ordering Information for the standard part numbers available; customization available upon request.  
\*Not a standard product, but is available upon request.

ORDERING INFORMATION

Aramus Assemblies (2-port): part number

SU - 2D -



Main connectors

- L11 = Luer-1: female 1: female
- L12 = Luer-1: female 2: male
- L22 = Luer-2: male 2: male

Tube length

- 0 = 6"
- 1 = 12"
- 2 = 18"
- 3 = 24"

Tube material

- F = AdvantaFlex thermoplastic elastomer
- P = AdvantaSil silicone
- S = Tygon silicone
- T = C-Flex 374 elastomer

Volume

- 0.020 = 20 mL
- 0.050 = 50 mL
- 0.100 = 100 mL
- 0.250 = 250 mL

Product type


- 2D = 2D bag

Product family

- SU = Single-use

Fasteners

- O = Oetiker SS ear clamps
- B = BarbLock clamps
- Z = Zip ties\*



Notes: Assemblies sold sterilized and are individually double bagged.  
\*Not a standard product, but is available upon request.

SU - 2D - -

O = Oetiker SS  
ear clamps  
B = BarbLock  
clamps  
Z = Zip ties\*

1 = Luer female  
2 = Luer male

CFM = MPC – *A*: female    *B*: male  
CFF = MPC – *A*: female    *B*: female  
CMF = MPC – *A*: male    *B*: female  
CMM = MPC – *A*: male    *B*: male

e length


$$\begin{aligned} 0 &= 6'' \\ 1 &= 12'' \\ 2 &= 18'' \\ 3 &= 24'' \end{aligned}$$

F = AdvantaFlex thermoplastic elastomer  
P = AdvantaSil silicone  
S = Tygon silicone  
T = C-Flex 374 elastomer

00.5 = 500 mL  
0001 = 1 liter  
0002 = 2 liter  
0005 = 5 L  
0010 = 10 L  
0020 = 20 L  
0050 = 50 L\*

2D = 2D bag

SU = Single-use



\*Not a standard product, but is available upon request.

## ORDERING INFORMATION (CONTINUED)

Aramus Subassemblies (2-port): part number

SU - 2D -	-U	
		<b>Volume</b>
		0.020 = 20 mL
		0.050 = 50 mL
		0.100 = 100 mL
		0.250 = 250 mL
	<b>Product type</b>	
	2D = 2D bag	
<b>Product family</b>		
SU = Single-use		

Note: Subassemblies sold unsterilized.

Aramus Subassemblies (3-port): part number

SU - 2D -	-U	
		<b>Volume</b>
		00.5 = 500 mL
		0001 = 1 L
		0002 = 2 L
		0005 = 5 L
		0010 = 10 L
		0020 = 20 L
		0050 = 50 L*
	<b>Product type</b>	
	2D = 2D bag	
<b>Product family</b>		
SU = Single-use		

Note: Subassemblies sold unsterilized.

\*Not a standard product, but is available upon request.

## FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit [entegris.com](https://www.entegris.com) and select the [Contact Us](#) link to find the customer service center nearest you.

## TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit [entegris.com](https://www.entegris.com) and select the [Terms & Conditions](#) link in the footer.



3265 Sunset Lane Hatboro, PA 19040 | 215-675-5700 | [sentinelprocess.com](https://www.sentinelprocess.com)

### Corporate Headquarters

129 Concord Road  
Billerica, MA 01821  
USA

### Customer Service

Tel +1 952 556 4181  
Fax +1 952 556 8022  
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design®, and other product names are trademarks of Entegris, Inc. as listed on [entegris.com/trademarks](https://www.entegris.com/trademarks). All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner.

©2016-2022 Entegris, Inc. | All rights reserved. | Printed in the USA | 9000-8098ENT-1122